

TECHNICAL DATA
RR 50 ENDURO
CHASSIS

Frame	steel double cradle frame
Wheel base	1385 mm
Max length	2052 mm
Max width	805 mm
Max height	1190 mm
Seat height	930 mm
Ground clearance	345 mm
Footrest height	395 mm
Dry weight	85 kg
Fuel tank capacity	6,5 l.
Reserve	1 l.
Cooling system capacity	620 cc
Front suspension	Hydraulic fork with ø37 mm shaft
Rear suspension	Monoshock
Shock absorber stroke	50 mm
Front wheel travel	210 mm
Rear wheel travel	200 mm
Front brake	disc ø260 mm
Rear brake	disc ø220 mm
Front rim	21 x 1,6 - 36 holes
Rear rim	18 x 1,85 - 36 holes
Front tyre	80/90 - 21
Rear tyre	110/80 - 18

ENGINE

Type	Single-cylinder, 2-stroke, liquid cooled, lamellar induction in the crankcase
Bore	40,3 mm
Stroke	39 mm
Displacement	49,7cc
Compression ratio	12:1
Ignition	Electronic Moric 12v - 100W
Spark plug	NGK BR9 ES
Lubrication	Mixing with mechanical pump, fuel 1,5% (with synthetic oil)
Feeding	with carburettor
Carburettor	Dell'Orto PHBN 16 HS
Clutch	Wet multi-disc clutch
Primary trasmission	Z. 20/71
Transmission	6 speed
Secondary Trasmission	Z. 11/51
Consumption l/100 km	3,43
Pollution Co2 [g/km]	78